

TSW200 TELTONIKA Industrial Unmanaged PoE+ Switch



Kode : TSW200
Brand : Teltonika
Jenis : Switch Unmanaged POE
Harga : Rp 1.673.000,00

TSW200 is an unmanaged industrial switch with 2 SFP ports for long-range Fiber-optic communication and 8 Gigabit Ethernet ports that support IEEE802.af and IEEE802.3at Power-over-Ethernet standards. Classified as power source equipment (PSE), it enables the centralization of the power supply, providing up to 30 watts per port and reducing the effort to install power.

***Belum termasuk power adaptor**

Penawaran Harga Spesial

 08112039555

Compatible Power Adaptor :

- [Power Adaptor DC 2-PIN 48 Volt 60 Watt 1.25 A](#)

- [Power Adaptor DC 2-PIN 48 Volt 120 Watt 2.5A](#)

Features :

- 2 x SFP ports for long-range Fiber-optic communication
- 8 x PoE+ ports with 802.af, 802.3at standard support
- Total power budget at PSE up to 240 W
- 8 x Gigabit Ethernet with speeds up to 1000 Mbps



Specification

| | |
|--|---|
| Model | TSW200 |
| ETHERNET | |
| LAN | 8 x ETH ports, 10/100/1000 Mbps, supports auto MDI/MDIX crossover |
| Fiber | 2 x SFP ports |
| IEEE 802.3 series standards | 802.3i, 802.3u, 802.3ab, 802.3x, 802.3az, 802.3ad |
| POE | |
| PoE ports | Port 1-8 |
| PoE standards | 802.3af and 802.3at |
| PoE Max Power per Port (at PSE) | 30 W |
| PoE Power Budget (at PSE) | 240 W |
| PERFORMANCE SPECIFICATIONS | |
| Bandwidth (Non-blocking) | 20 Gbps |
| Packer buffer | 128 KB |
| MAC address table size | 2K entries |
| Jumbo frame support | 9216 bytes |
| POWER | |
| Connector | 2-pin industrial DC power socket |
| Input voltage range | 7 - 57 VDC |
| Input voltage range for PoE | 44 - 57 VDC |
| Power consumption | Idle: 1.81 W / Max: 5.5 W / PoE Max: 245.5 W |
| PHYSICAL INTERFACES | |
| Ethernet | 8 x RJ45 ports, 10/100/1000 Mbps |
| Fiber | 2 x SFP ports |
| Status LEDs | 1 x Power LED, 16 x LAN status LEDs 2 x SFP status LEDs |
| Power | 1 x 2-pin industrial DC power socket |
| Other | 1 x Grounding screw |

| PHYSICAL SPECIFICATION | |
|----------------------------------|---|
| Casing material | Full aluminum housing |
| Dimensions (W x H x D) | 132 x 44.2 x 95.1 mm |
| Mounting options | DIN rail or wall mounting (additional kit needed), flat surface placement |
| OPERATING ENVIRONMENT | |
| Operating temperature | -40 °C to 75 °C |
| Operating humidity | 10% to 90% non-condensing |
| Ingress Protection Rating | IP30 |

Standard Package Contains :

- TSW200
- QSG (Quick Start Guide)
- Packaging box

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1063/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com