

RG-RAP1261 REYEE Wi-Fi 6 AX3000 Ultra-Thin Wall Plate Access Point



Kode : RG-RAP1261
Brand : Ruijie - Reyee
Jenis : Wireless Indoor

RG-RAP1261 Ruijie Reyee Wi-Fi 6 AX3000 Ultra-Thin Wall Plate Access Point.

***Belum termasuk adaptor dan poe injector.**

***Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial

 **08112039555**

- Wi-Fi 6, 2976Mbps, 2* GE, 86mm Ultra-Thin Design.
- Dual-radio performance, gigabit wireless wall-mounted AP.
- Better experience with Cooling Patent Technology.
- Easy installation, 86mm standard compatible.
- Capable of Reyee Mesh and 802.11K/V.
- Powerful Standalone Portal via Ruijie Cloud.



Specification

| | |
|------------------------|-----------------------------------|
| Model | RG-RAP1261 |
| Wi-Fi Standards | 802.11a/n/ac/ax 802.11b/g/n/ax |

| | |
|--|---|
| MIMO | 2.4 GHz, 2x2, MU-MIMO 5 GHz, 2x2, MU-MIMO |
| Max. Data Rate | 2.4 GHz: 574 Mbps 5 GHz: 2402 Mbps |
| Number of Antennas | 5 |
| Antenna Type | Built-in omnidirectional antennas |
| Antenna Gain | 2.4 GHz: 1.6 dBi 5 GHz:: 4.13 dBi Note The peak gain mentioned above refers to the gain of a single antenna |
| Transmit Power | 2.4 GHz: 20 dBm 5 GHz: 30 dBm Note The transmitted power may vary based on local laws and regulations. |
| Fixed Ports | 1 x 10/100/1000Base-T Ethernet uplink port 1 x 10/100/1000Base-T Ethernet downlink ports 1 x Reset hole |
| Max. Number of Concurrent STAs | 512 |
| Recommended Number of Concurrent STAs | 110 |
| Max. Number of SSIDs | 8 |
| Supported Frequency Bands | 802.11b/g/n/ax: 2.400 GHz to 2.483 GHz 802.11a/n/ac/ax: 5.150 GHz to 5.350 GHz, 5.470 GHz to 5.725 GHz, 5.725 GHz to 5.850 GHz Note: Country-specific restrictions apply |
| Channel Bandwidth | 2.4 GHz: Auto/20 MHz/40 MHz 5 GHz: Auto/20 MHz/40 MHz/80 MHz/160 MHz |
| Roaming | Layer 2 roaming Layer 3 roaming 802.11k/v roaming |
| Security Mode | WAP-PSK, WAP2-PSK, and WPA-WAP2-PSK |
| Network Access Mode | PPPoE Client DHCP Client Static IP |
| VLAN | Port-based VLAN VLAN over 802.1Q TV projection screen |
| LED | 1 x System status LED |
| Reset Hole | 1 x Reset hole |
| Dimensions (W x D x H) | 86 mm x 86 mm x 42.4 mm (3.39 in. x 3.39 in. x 1.67 in.) |
| Installation Method | In-wall mounting |

| | |
|--|----------------------------------|
| Power Supply | IEEE 802.3af/at PoE |
| Max. Power Consumption | 10.2 W |
| Operating Temperature | 0°C to 40°C (32°F to 104°F) |
| Storage Temperature | -40°C to +70°C (-40°F to +158°F) |
| Operating Humidity | 5% to 95% RH (non-condensing) |
| Storage Humidity | 5% to 95% RH (non-condensing) |
| Ingress Protection Rating (IP Rating) | IP41 |
| Surge Protection | +/-4kV |
| MTBF | 400,000 hours |

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1065/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com