CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

FD514GB-X-R410 C-DATA 4GE XPON ONU (MDU)



Kode : FD514GB-X-R410
Brand : C-Data
Jenis : FTTH ONT/ONU/MDU
Harga : Rp 435.000,00

FD514GB-X-R410 CDATA is an indoor fiber broadband access terminal. The device provides one GPON / EPON adaptive optical port and supports XPON mode. It can be used in connection with our company FD16/17 series GPON OLT or FD12 / 13 series EPON OLT. It can also interconnect with the mainstream manufacture (Huawei / ZTE / Fiberhome) GPON or EPON OLT to provide users with Internet service based on GPON and EPON technology.

- **In compliant with IEEE802.3ah and ITU - T G.984 standard**
- **Support ONU auto-discovery/Link detection/remote upgrade of software**
- **Support SN and LOID+Password multiple registration methods**
- **Support port-based rate limitation and bandwidth control**
- **Support Dynamic Bandwidth Allocation (DBA)**
- **EMS network management based on SNMP ,convenient for maintenance**
- **Support power-off alarm function, easy for link problem detection**
- **Single-fiber access, provides internet service.**

Specification

Model	FD514GB-X-R410
User Port (LAN)	4x 10/100/1000Mbps adaptive Ethernet port Full/half duplex Auto MDI/MDI-X
Indicators	PWR / PON / LOS / LAN / RSV
PON Mode	EPON : 1000BASE-PX20+ symmetric GPON : FSAN G.984.2 standard,Class B+
PON Rate	EPON : 1.25Gbps (downstream/upstream) GPON : 2.488Gbps/1.244Gbps (downstream/upstream)
Wavelength	Transmit : 1310nm Receiver : 1490nm

www.citraweb.com

Receiving sensitivity	EPON : -27dBm GPON : -28dBm
Saturated power	EPON : -3dBm GPON : -8dBm
Transmitting power	EPON : 0 ~ 4dBm GPON : 0.5 ~ 5dBm
Operating temperature	-30 to 65ºC
Operating humidity	10% ~ 90% (Non-condensing)

Download Datasheet

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1242/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com