

# RG-RAP72Pro REYEE Wi-Fi 7 BE5040 Dual-Band Ceiling Access Point



**Kode** : RG-RAP72Pro

**Brand** : Ruijie - Reeye

**Jenis** : Wireless Indoor

RG-RAP72Pro Ruijie Reeye Wi-Fi 7 BE5040 Dual-Band Ceiling Access Point.

**\*Belum termasuk adaptor dan poe injector**

**\*Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

**Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.**

Penawaran Harga Spesial

 **08112039555**

## Product Highlights :

- Next-generation performance with Wi-Fi 7, delivering extra-high wireless speeds
- Superior streaming with Wi-Fi 7's exclusive MLO feature
- Compact design and easy installation
- Enhanced data transmission with 4K-QAM for faster speeds
- Ideal for integrating with enterprise switches to create a robust office network



## Specification

|              |             |
|--------------|-------------|
| <b>Model</b> | RG-RAP72Pro |
|--------------|-------------|

|                              |  |
|------------------------------|--|
| <b>Wi-Fi Standards</b>       | Wi-Fi 4: IEEE 802.11a/b/g/n<br>Wi-Fi 5: IEEE 802.11ac Wave 2<br>Wi-Fi 6: IEEE 802.11ax<br>Wi-Fi 7: IEEE 802.11be |
| <b>Spatial Streams</b>       | 2.4GHz, 2x2 MU-MIMO<br>5GHz, 3x3 MU-MIMO   |
| <b>Data Rate</b>             | Max. throughput: 5011Mbps<br>2.4 GHz: 688Mbps<br>5 GHz: 4323Mbps   |
| <b>Antenna</b>               | Built-in<br>Antenna gain: 2.4 GHz, 2.0 dBi; 5 GHz, 3 dBi   |
| <b>Channel Width</b>         | 2.4 GHz: Auto/20/40 MHz<br>5 GHz: Auto/20/40/80/160 MHz  |
| <b>Transmit Power</b>        | 2400-2483.5 MHz, EIRP ≤ 27 dBm<br>5150-5350 MHz, EIRP ≤ 23 dBm<br>5725-5825 MHz, EIRP ≤ 23 dBm                   |
| <b>Service Ports</b>         | 1 x 10/100/1000BASE-T port<br>1 x 10/100/1000/2500BASE-T port  |
| <b>Max. Clients</b>          | 512  |
| <b>Recommended Clients</b>   | 110  |
| <b>Max. SSIDs</b>            | 8  |
| <b>Operating Mode</b>        | AP mode and router mode  |
| <b>Dimensions</b>            | 208mm x 208mm x 40mm (8.19in. x 8.19in. x 1.57in.)(excluding the mounting bracket)                               |
| <b>Installation</b>          | Ceiling-mount or wall-mount  |
| <b>Power Supplies</b>        | IEEE 802.3at standard PoE or DC (12 V, 2.5 A)power supply  |
| <b>Power Consumption</b>     | ≤ 30W  |
| <b>Operating Temperature</b> | 0°C to 40°C  |
| <b>Storage Temperature</b>   | -40°C to 70°C  |
| <b>Operating Humidity</b>    | 5% to 95% Noncondensing  |
| <b>Storage Humidity</b>      | 5% to 95% Noncondensing  |
| <b>Surge Protection</b>      | +/-2kV   |
| <b>MTBF</b>                  | >400000H   |

[Download Datasheet](#)

\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

**URL :** <https://www.citraweb.com/produk/1272/>

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email [sales@citraweb.com](mailto:sales@citraweb.com)**

[www.citraweb.com](http://www.citraweb.com)