

FD1700S C-DATA 8PON 4SFP+ 4SFP28 Expandable GPON OLT

Kode : FD1700S-PDX0-8T

Brand : C-Data

Jenis : FTTH OLT

Harga : Rp 23.000.000,00



The GPON OLT FD1700S CDATA fully complies with the relevant standards of ITU G.984.x and FSAN. It's a 1RU device featuring an uplink SFP port with options for either 4*1G/10G and 4*10G/25G. The PON ports come in configurations of 8 ports. Each GPON port supports a splitting ratio of 1:128. Consequently, the GPON system can accommodate up to 4096 terminal connections, depending on the number of PON ports chosen.

Penawaran Harga Spesial

08112039555



Specification

| | |
|--------------------|---|
| Model | FD1700S-PDX0 |
| Uplink Port | 4*1G(SFP)/10G SFP+ 4*10G(SFP+)/25G(SFP28) |
| PON Port | 8* GPON |
| | Physical interface : SFP slot |
| | Interface type : ITU-TG.984.2 Class B+/Class C+ |
| | Max splitting ratio : GPON: 1:128 |

| | |
|---------------------------------|---|
| Management Port | 1* 100/1000BASE-Tx out-band Ethernet port 1* CONSOLE local management port |
| Transmission distance | 20KM |
| Port rate | GPON: Downstream: 2.5Gbps Upstream: 1.25Gbps |
| Wavelength | Forwarding: 1490nm Receiving: 1310nm |
| Interface type | SC/UPC |
| Fiber type | 9/125µm SMF (Single Mode Fiber) |
| Light transmission power | Class B+ : +1.5~+5dBm Class C+ : +3 ~ +7dBm |
| Receiving sensitivity | Class B+ : -28dBm Class C+ : -30dBm |
| Saturation power | Class B+ : -8dBm Class C+ : -12dBm |
| Backplane Bandwidth | 400G |
| Power supply | AC : 100V ~ 240V?47~63Hz DC : -40V ~ -72V |
| Working temperature | -15 ~ 50 C |
| Storage temperature | -40 ~ 85 C |
| Ambient humidity | 5 ~ 90% (Non-condensing) |

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1285/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com