

FD511G-X-F670 C-DATA 1GE XPON ONU

Kode : FD511G-X-F670

Brand : C-Data

Jenis : FTTH ONT/ONU/MDU

Harga : Rp 180.000,00



FD511G-X-F670 C-DATA dual-mode ONU supports EPON and GPON two modes access. The ONU automatically switches into the corresponding PON mode by identifying the local OLT mode to complete GPON or EPON adaptive access. FD511G-X-F670 features high-performance forwarding capabilities to ensure excellent experience with Internet and HD video services.

Penawaran Harga Spesial

08112039555

- In compliant with IEEE802.3ah and ITU - T G.984 standard
- Support ONU auto-discovery/Link detection/remote upgrade of software
- Support multiple registration methods
- Support port VLAN configuration
- Support mac-address learning
- Support port-based rate limitation and bandwidth control
- Support port flow-control
- Support broadcasting storm resistance function
- Support igmp transparent/snooping/proxymode
- Support Dynamic Bandwidth Allocation(DBA)
- Support three layer routing function
- EMS network management based on SNMP ,convenient for maintenance
- Support power-off alarm function ,easy for linkproblem detection

Specification

| | |
|------------------------------|---|
| Model | FD511G-X-F670 |
| GPON/EPON Port | Single mode single fiber GPON : FSAN G.984.2 standard, Class B+ EPON : 1000BASE-PX20+ symmetric |
| Downstream/Upstream | GPON : 2.488Gbps/1.244Gbps EPON : 1.25Gbps |
| Wavelength | Transmit : 1310nm Receiver : 1490nm |
| Receiving sensitivity | GPON : -28dBm EPON : -27dBm |

| | |
|------------------------------|---|
| Saturated power | GPON : -8dBm EPON : -3dBm |
| Transmitting power | GPON : 0.5 ~ 5dBm EPON : 0 ~ 4dBm |
| User Port (LAN) | 1*10/100/1000M Auto-negotiation RJ45 ports Full/half duplex RJ45, Auto-MDI/MDI-X Transmission Distance 100 Meter |
| Power | External 12V/0.5A DC power supply adapter |
| Power consumption | <3W |
| Operating temperature | 0 to 40°C |
| Item Dimension | 78 x 78 x 23.5 mm |
| Operating humidity | 10% to 90%(Non-condensing) |

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1287/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com