

V1600GT V-SOL 2PON GPON OLT

Kode : V1600GT

Brand : V-Sol

Jenis : FTTH OLT

Harga : Rp 6.250.000,00

Rp 7.450.000,00



The V1600GT vsol is a box-type GPON OLT with two GPON ports that meets flexible and fast FTTx access, suiting the scenarios such as sparse/remote/cost-sensitive area, smart industrial park, commercial building and FTTH, etc.

2*GE(RJ45)+2*GE(SFP)/10GE(SFP+)
***Sudah termasuk 2x SFP 9dBm**

Penawaran Harga Spesial

 **08112039555**

Specification

| | |
|-----------------------------------|---|
| Model | V1600GT |
| Uplink Port | QTY : 4 |
| | RJ45(1G) : 2 |
| | SFP(1G)/SFP+(10G) : 2 |
| GPON Port | QTY : 2 |
| | Physical Interface : SFP Slots |
| | Supported PON module level : Class C++/Class C+++ /Class C++++ |
| | Max splitting ratio : 1:128 |
| Management Port | 1*10/100/1000 BASE-T out-band port, 1*CONSOLE port, 1*USB-COM, 1*USB2.0 |
| Backplane Bandwidth (Gbps) | 208 |
| Port Forwarding Rate(Mpps) | 40.176 |

| | |
|--|--|
| PON Port Specification (Class C+++) | Transmission Distance : 20KM |
| | PON port speed : Upstream 1.244Gbps Downstream 2.488Gbps |
| | Wavelength TX 1490nm RX 1310nm |
| | Connector : SC/UPC |
| | Fiber Type : 9/125µm SMF |
| | TX Power : +4.5~+10dBm |
| | Rx Sensitivity : ≤ -30dBm |
| | Saturation Optical Power : -12dBm |
| Power supply | AC : Working Voltage Range: 100~240V, Rated Voltage: 110V/220V DC : 48V |
| Management Mode | WEB , Telnet , CLI |
| Working temperature | -20 ~ +60 C |
| Storage temperature | -40 ~ +70 C |
| Relative Humidity | 5 ~ 95% (Non-condensing) |
| Dimension (L*W*H) | 442 x 200 x 43.6 mm |

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1290/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com