

# V2801RGW V-SOL 1XPON 1GE WIFI4 ONU


**Kode** : V2801RGW

**Brand** : V-Sol

**Jenis** : FTTH ONT/ONU/MDU

**Harga** :

1 - 19 : Rp 240.000,00

20 - ... : Rp 235.000,00

V2801RGW vsol (1GE+WiFi 4 XPON ONT) is specially designed to meet the access requirements of telecom operators such as FTTH and SOHO. The ONT is based on a high-performance chip solution (Realtek), supports mature IEEE 802.11 b/g/n WiFi 4 technology, and also supports Layer 2/Layer 3 functions, providing data services for carrier-grade FTTH applications.

## 1\*GE+WiFi4

**\*Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

Penawaran Harga Spesial

 **08112039555**

## Key Features :

- Realtek Chipset High Performance Solution
- IEEE802.3ah EPON or ITU-TG.984.X GPON Standard
- WiFi IEEE802.11b/g/n 2T2R 5dBi Antenna
- Powerful Firewall

## Specification

|                       |   |
|-----------------------|---|
| <b>Model</b>          | V2801RGW  |
| <b>PON Interface</b>  | <ul style="list-style-type: none"> <li>• 1 XPON port(EPON PX20+ &amp; GPON Class B+)</li> <li>• SC single mode, SC/UPC connector</li> <li>• TX optical power : 0~+4dBm</li> <li>• RX sensitivity : -27dBm</li> <li>• Overload optical power : -3dBm(EPON) or -8dBm(GPON)</li> <li>• Transmission distance : 20KM</li> </ul> |
| <b>Wifi Interface</b> | <ul style="list-style-type: none"> <li>• IEEE802.11b/g/n(TX power:17dBm/16dBm/ 15dBm), 300Mbps</li> <li>• Support 13 Channels</li> </ul>  |
| <b>LAN interface</b>  | 1*GE Auto-negotiation RJ45 ports  |
| <b>PON mode</b>       | XPON Dual Mode , Can access mainstream EPON/GPON OLTs   |

|                            |  |
|----------------------------|--|
| <b>Software Mode</b>       | Routing Mode   |
| <b>Multicast</b>           | IGMP v1/v2/v3 , IGMP snooping  |
| <b>Firewall</b>            | DDOS, Filtering Based on ACL/MAC/ URL  |
| <b>Layer2</b>              | 802.1D&802.1ad bridge, 802.1p Cos, 802.1Q VLAN   |
| <b>Layer3</b>              | IPv4/IPv6, DHCP Client/Server, PPPoE, NAT, DMZ, DDNS   |
| <b>WiFi</b>                | <ul style="list-style-type: none"> <li>• WiFi Authentication : WEP/WAP-PSK(TKIP)/WAP2-PSK(AES)</li> <li>• Support : multiple SSID</li> </ul> |
| <b>Security</b>            | <ul style="list-style-type: none"> <li>• Flow &amp; Storm control, Loop Detection</li> </ul>   |
| <b>O&amp;M</b>             | WEB/TELNET/OAM/OMCI/TR069  |
| <b>Dimension</b>           | 120mm×78mm×30mm(L×W×H)   |
| <b>Power adapter</b>       | DC 12V, 1A, external AC-DC power adaptor   |
| <b>Power supply</b>        | ≤6W  |
| <b>Operating condition</b> | Operating temp : -10 ~ +55C<br>Operating humidity : 5 ~ 95% (non-condensing)   |
| <b>Storing condition</b>   | Storing temp: -40 ~ +70C<br>Storing humidity: 5 ~ 95% (non-condensing)   |
| <b>Indicators</b>          | POWER, LOS, PON, LAN, WiFi   |

[Download Datasheet](#)

\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

**URL :** <https://www.citraweb.com/produk/1300/>

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email [sales@citraweb.com](mailto:sales@citraweb.com)**