

Dream Machine Special Edition UNIFI UBIQUITI

Kode : UDM-SE

Brand : Ubiquiti

Jenis : Router Rackmount

Harga : Rp 9.836.000,00



Dream Machine Special Edition 10G Cloud Gateway with 100+ UniFi device / 1,000+ client support, 3.5 Gbps IPS routing, and built-in PoE switching.

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial

 **08112039555**



Specification

| | |
|--------------|--------|
| Model | UDM-SE |
|--------------|--------|

| | |
|---|---|
| Processor | Quad-core ARM Cortex-A57 at 1.7 GHz |
| System Memory | 4 GB |
| On-board Storage | 16 GB eMMC 128 GB SSD (Integrated) |
| Ports | 1 GbE RJ45 : 8 (1G/100M/10M) 2.5 GbE RJ45 : 1 (2.5G/1G/100M/10M) 10G SFP+ : 2 (10G/1G) |
| PoE Budget | 180W |
| Max. PoE Wattage per Port by PSE | PoE : 15.4W PoE+ : 30W |
| Voltage Range PoE Mode | PoE: 44-57V PoE+: 50-57V |
| Max. Power Consumption | 50W (Excluding PoE Output) |
| Form Factor | Rack mount (1U) |
| Managed UniFi Devices | 100+ |
| Managed Cameras | (24) HD (14) 2K (8) 4K |
| Managed Access Hubs | 150 |
| Simultaneous Users Connected | 1,000+ |
| Max. WAN Port Count | 8 |
| Default WAN Ports | (1) 10G SFP+ (1) 2.5 GbE RJ45 |
| IDS/IPS Throughput | 3.5 Gbps |
| Redundancy | Shadow Mode (VRRP) Gateway Failover DC Power Backup |
| MAC Address Table Size | 4,000 |
| NVR Storage | (1) 3.5" NVR HDD bay Built-in 128 GB SSD for Faster Experience |
| Power Method | (1) Universal AC input, 100–240V AC, 4.4A Max., 50/60 Hz (1) USP-RPS DC input, 52V DC, 3.94A |
| Power Supply | AC/DC, internal, 240W |
| Supported Voltage Range | 100–240V AC |
| Dimensions (W x D x H) | 442.4 x 43.7 x 285.6 mm (17.4 x 1.7 x 11.2") |
| Enclosure Material | Aluminium CNC, SGCC steel |
| Mount Material | SGCC steel |

| | |
|--------------------------------------|--|
| LCM Display | 1.3" touchscreen |
| Management | Ethernet Bluetooth |
| Button | (1) Factory-reset |
| ESD/EMP Protection | Air: $\pm 15\text{kV}$, contact: $\pm 8\text{kV}$ |
| Ambient Operating Temperature | -10 to 40° C (14 to 104° F) |
| Ambient Operating Humidity | 5 to 95% noncondensing |
| Certifications | CE, FCC, IC, Anatel, SRRC |

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1412/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com