

On Line UPS PlusPRO 4 3000VA/2700Watt Non Battery



Kode : PlusPRO 4-3000

Brand : Aplus

Jenis : UPS

Harga : Rp 8.700.000,00

~~Rp 10.000.000,00~~

PlusPRO 4-3000 adalah UPS **online true double conversion dengan rating 3000VA/2700Watt** yang menghadirkan **output pure sinewave** dengan **waktu perpindahan nol (zero transfer time)**. Dirancang fleksibel dalam satu perangkat yang dapat digunakan sebagai **rack-mount** maupun **tower**, seri ini memberikan perlindungan daya tingkat profesional.

***Penjualan produk ini tidak termasuk battery**

Penawaran Harga Spesial

 **08112039555**

Features :

- Intelligent Slot (SNMP) + USB multiple communications included
- High performance true double conversion On Line UPS 1-3KVA
- External battery bank to extend back-up time (Optional)
- Microprocessor control guarantees high reliability
- Low heat dissipation in long time operation
- RS-232 port multiple communications
- High efficiency mode (ECO mode)
- Output voltage regulation +/-1%
- Automatic self-testing function
- Power management software
- Output power factor 0.9
- Wide input range
- Fan speed control
- DC start





Battery Type :

- VRLA 12V/7AH atau 12V/9AH
- 6 pcs
- Rated Battery Voltage 72VDC
- **Battery dimension 151 x 65 x 100 mm**

Extend Battery Box :
Battery Box BBR2B-96V Maksimal 6 battery (72VDC)

Specification :

| INPUT | |
|---------------------------------|--|
| Voltage | 1 Phase 2 Wires with Ground 220/230/240Vac |
| Voltage Range | 110-300Vac |
| Frequency | 50Hz or 60Hz (Auto-Sensing) |
| Type of Connection | IEC-320 C20 connection & EU plug power cable |
| OUTPUT | |
| Voltage | 220/230/240Vac |
| Voltage Range | +/- 1% |
| Frequency (Battery Mode) | 50Hz or 60Hz +/- 0.05Hz |

| | |
|--------------------------------------|---|
| Waveform | Pure Sinewave |
| THD | <2%(linear load) |
| Crest Ratio | 3:1 |
| EFFICIENCY | |
| Inverter Mode | >90% |
| BATTERY | |
| Voltage | 72VDC |
| Type | VRLA 12V/7AH *6pcs or 12V/7AH *6pcs |
| Recharge Time | 5 hours to 90% |
| External Battery Connectors | 72VDC |
| TRANSFER TIME | |
| Battery Mode to Inverter Mode | 0ms |
| Inverter to Bypass | <4ms |
| DISPLAY | |
| LCD Display | Input, Output, Load, Battery, Mode/Fault/Warning code, Inverter operating, Bypass operating, Output voltage and frequency and Bypass disable/enable selection information |
| AUDIBLE ALARM | |
| Battery Mode | Beeps Every 4 Seconds |
| Low Battery | Sounding Every Second |
| Overload | Sounding Twice Every Second |
| Fault | Beeping continuously |
| COMMUNICATIONS | |
| Interface (Port) | RS-232 |
| USB Port | Yes |
| Intelligent Slot (SNMP port) | Yes |

| | |
|------------------------------|-----------------------|
| SNMP Card | SNMP MINI card |
| ENVIRONMENT | |
| Operating Temperature | 0°C-40°C |
| Humidity | <95% (Non-condensing) |
| Acoustic Noise | <50db at 1M |
| PHYSICAL | |
| Rack Height | Tower/Rack: 2U |
| Dimension (W*D*H) | 568*440*88(2U)mm |

Manual :

[PlusPro4-3000/2700 Manual](#)

Brochure :

[PlusPro4-3000/2700 Brochure](#)

Battery Installation Guide :

[Aplus_Plus_battery_Installation.pdf](#)

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : <https://www.citraweb.com/produk/1435/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com