

On Line UPS PlusPRO 4 3000VA/2700Watt



Kode : PlusPRO 4-3000(B)

Brand : Aplus

Jenis : UPS

Harga : Rp 10.500.000,00

~~Rp 12.500.000,00~~

PlusPRO 4-3000 adalah UPS **online true double conversion** dengan **rating 3000VA/2700Watt** yang menghadirkan **output pure sinewave** dengan **waktu perpindahan nol (zero transfer time)**. Dirancang fleksibel dalam satu perangkat yang dapat digunakan sebagai **rack-mount** maupun **tower**, seri ini memberikan perlindungan daya tingkat profesional.

***Produk sudah termasuk 6 pcs battery 12V/9AH**

***Garansi produk 1 Tahun**

***Garansi battery 1 Bulan**

Penawaran Harga Spesial

 **08112039555**

Features :

- Intelligent Slot (SNMP) + USB multiple communications included
- High performance true double conversion On Line UPS 1-3KVA
- External battery bank to extend back-up time (Optional)
- Microprocessor control guarantees high reliability
- Low heat dissipation in long time operation
- RS-232 port multiple communications
- High efficiency mode (ECO mode)
- Output voltage regulation +/-1%
- Automatic self-testing function
- Power management software
- Output power factor 0.9
- Wide input range
- Fan speed control
- DC start





Battery Type :

- VRLA 12V/7AH atau 12V/9AH
- 6 pcs
- Rated Battery Voltage 72VDC
- **Battery dimension 151 x 65 x 100 mm**

Extend Battery Box :
Battery Box BBR2B-96V Maksimal 6 battery (72VDC)

Specification :

INPUT	
Voltage	1 Phase 2 Wires with Ground 220/230/240Vac
Voltage Range	110-300Vac
Frequency	50Hz or 60Hz (Auto-Sensing)
Type of Connection	IEC-320 C20 connection & EU plug power cable
OUTPUT	
Voltage	220/230/240Vac
Voltage Range	+/- 1%
Frequency (Battery Mode)	50Hz or 60Hz +/- 0.05Hz

Waveform	Pure Sinewave
THD	<2%(linear load)
Crest Ratio	3:1
EFFICIENCY	
Inverter Mode	>90%
BATTERY	
Voltage	72VDC
Type	VRLA 12V/7AH *6pcs or 12V/7AH *6pcs
Recharge Time	5 hours to 90%
External Battery Connectors	72VDC
TRANSFER TIME	
Battery Mode to Inverter Mode	0ms
Inverter to Bypass	<4ms
DISPLAY	
LCD Display	Input, Output, Load, Battery, Mode/Fault/Warning code, Inverter operating, Bypass operating, Output voltage and frequency and Bypass disable/enable selection information
AUDIBLE ALARM	
Battery Mode	Beeps Every 4 Seconds
Low Battery	Sounding Every Second
Overload	Sounding Twice Every Second
Fault	Beeping continuously
COMMUNICATIONS	
Interface (Port)	RS-232
USB Port	Yes
Intelligent Slot (SNMP port)	Yes

SNMP Card	SNMP MINI card
ENVIRONMENT	
Operating Temperature	0°C-40°C
Humidity	<95% (Non-condensing)
Acoustic Noise	<50db at 1M
PHYSICAL	
Rack Height	Tower/Rack: 2U
Dimension (W*D*H)	568*440*88(2U)mm

Manual :

[PlusPro4-3000/2700 Manual](#)

Brochure :

[PlusPro4-3000/2700 Brochure](#)

Battery Installation Guide :

[Aplus_Plus_battery_Installation.pdf](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1481/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com