CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

eKitEngine AP661 HUAWEI Triple-Radio Ultra-High-Speed 6575 Mbps Wi-Fi 6 Access Point



Kode : AP661
Brand : Huawei
Jenis : Wireless Indoor
Harga : Rp 3.445.000,00

HUAWEI eKitEngine AP661 adalah Access Point indoor berteknologi Wi-Fi 6 (802.11ax) yang mampu menyalurkan sinyal secara simultan di frekuensi 2.4 GHz (2x2) serta 5 GHz (2x2 dan 4x4) dengan kecepatan total hingga 6,575 Gbps. Dibekali antena pintar terintegrasi untuk menjaga kestabilan sinyal secara optimal.

***Belum termasuk adaptor dan poe injector**

***Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial
08112039555

- Settled AP
- Wi-Fi 6
- 6.575 Gbps device rate
- Tri-radio
- 300 access users recommended
- Max. 1536 access users
- 26 dBm transmit power
- Smart antenna
- 30 m optimal coverage range

www.citraweb.com









www.citraweb.com

Spesifikasi

Model	AP661
Wi-Fi standard	2.4 GHz: 802.11b/g/n/ax 5 GHz: 802.11a/n/ac/ac Wave 2/ax
Optimal Signal Distance (m)	30
Max Number of Access Users	1536
Recommended Number of Access Users	300

Device Rate	6.575 Gbps
Maximum number of physical ports on the entire device	2.5GE (RJ45) x 1, 100M/1000M/2.5G auto-sensing GE (RJ45) x 1, 10M/100M/1000M auto-sensing
Radio number	3
Maximum channel bandwidth [MHz]	Radio 0 (2.4 GHz): 40 MHz Radio 1 (5 GHz-H): 80 MHz Radio 2 (5 GHz-L): 160 MHz
Maximum transmit power	2.4 GHz: 22 dBm/chain 25 dBm (combined power) 5 GHz (2x2): 20 dBm/chain 23 dBm (combined power) 5 GHz (4x4): 20 dBm/chain 26 dBm (combined power) BLE: < 10 dBm
MIMO spatial streams	Radio 0 (2.4 GHz): 2x2 Radio 1 (5 GHz-H): 2x2 (high frequency band: 5490–5850 MHz) Radio 2 (5 GHz-L): 4x4 (low frequency band: 5150–5330MHz)
Maximum power consumption [W]	21.2 (excluding USB), 802.3at/af power supply
Input voltage range [V]	DC: 12 V ± 10% PoE: 802.3at/af
Dimensions without packaging (H x W x D) [mm(in.)]	Diameter x depth: 220 mm x 50 mm (8.66 in. x 1.97 in.)
Long-term operating temperature [°C(°F)]	–10°C to +50°C (14°F to 122°F) (From 1800 m to 5000 m [5905.51 ft. to 16404.20 ft.], the maximum temperature of the device decreases by 1°C [1.8°F] for every 300 m [984.25 ft.] increase in altitude.)
Long-term operating relative humidity [RH]	5% RH to 95% RH, non-condensing
Radio interface	Built-in smart antennas
Antenna gain	2.4G: 4 dBi/chain (peak value) 2 dBi (combined gain) 5G: 5 dBi/chain (peak value) 3 dBi (combined gain) BLE: 4 dBi
Operating frequency band	2.4GHz,5GHz

www.citraweb.com

Download Datasheet

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1540/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com