CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

eKitEngine AP673E HUAWEI BE7900 Tri-Band Wi-Fi 7 High-Density Settled Access Point



Kode : AP673E
Brand : Huawei
Jenis : Wireless Indoor
Harga : Rp 3.955.000,00

HUAWEI eKitEngine AP673E BE7900 Tri-Band Wi-Fi 7 High-Density Settled Access Point adalah Access Point indoor berteknologi Wi-Fi 7 (802.11be) yang mendukung fitur mutakhir seperti MLO, MU-MIMO, dan 4096-QAM, serta bekerja simultan di frekuensi 2.4 GHz 2x2, 5 GHz 2x2, dan 5 GHz 4x4 dengan kecepatan total hingga 7,89 Gbps. Berdesain bulat elegan (220 mm) dengan bracket logam kokoh untuk kemudahan instalasi di dinding maupun langit-langit, AP ini mendukung manajemen lokal maupun *remote* berbasis aplikasi/cloud, menjadikannya solusi ideal dan efisien bagi UKM, hotel, serta sekolah.

***Belum termasuk adaptor dan poe injector**

***Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial
08112039555

- **Settled AP**
- **Wi-Fi 7**
- **7.89 Gbps device rate**
- **Tri-radio**
- **180 access users recommended**
- **Max. 1024 access users**
- **26 dBm transmit power**
- **Smart antenna**
- **30 m optimal coverage range**

www.citraweb.com

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com



Spesifikasi

Model	AP673E
Wi-Fi standard	2.4 GHz: 802.11b/g/n/ax/be 5 GHz: 802.11a/n/ac/ac Wave 2/ax/be 5 GHz: 802.11a/n/ac/ac Wave 2/ax/be
Optimal Signal Distance (m)	30
Max Number of Access Users	1024
Recommended Number of Access Users	180
Device Rate	7.89 Gbps
Maximum number of physical ports on the entire device	1x 5GE (RJ45) 100M/1000M/2500M/5000M auto-sensing 1x GE (RJ45) 10M/100M/1000M auto-sensing
Radio number	3
Maximum channel bandwidth [MHz]	Radio 0 (2.4 GHz): 40 MHz Radio 1 (5 GHz-H): 80 MHz Radio 2 (5 GHz-L): 160 MHz
Maximum transmit power	2.4 GHz: 20 dBm/chain 23 dBm (combined power) 5 GHz (2x2): 20 dBm/chain 23 dBm (combined power) 5 GHz (4x4): 20 dBm/chain 26 dBm (combined power)
MIMO spatial streams	Radio 0 (2.4 GHz): 2x2 Radio 1 (5 GHz-H): 2x2 (high frequency band: 5490–5850 MHz) Radio 2 (5 GHz-L): 4x4 (low frequency band: 5150–5330MHz)
Maximum power consumption [W]	22.3 (excluding USB and PoE out)

www.citraweb.com

Input voltage range [V]	DC: 43.2 V to 57.6 V PoE: 802.3bt/at/af
Dimensions without packaging (H x W x D) [mm(in.)]	Diameter x depth: 220 mm x 45 mm (8.66 in. x 1.77 in.)
Long-term operating temperature [°C(°F)]	–10°C to +50°C (14°F to 122°F) (From 1800 m to 5000 m [5905.51 ft. to 16404.20 ft.], the maximum temperature of the device decreases by 1°C [1.8°F] for every 300 m [984.25 ft.] increase in altitude.)
Long-term operating relative humidity [RH]	5% RH to 95% RH, non-condensing
Radio interface	Built-in smart antennas
Antenna gain	2.4 GHz: 4 dBi/chain (peak gain) 2 dBi (combined gain) 5 GHz-1: 5 dBi/chain (peak gain) 3 dBi (combined gain) 5 GHz-2: 5 dBi/chain (peak gain) 3 dBi (combined gain)
Operating frequency band	2.4GHz,5GHz

Download Datasheet

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1542/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com