

TP-LINK ES220GP OMADA 20-Port Gigabit Easy Managed Switch with 16-Port PoE+

Kode : ES220GP

Brand : TP-Link Omada

Jenis : Switch Managed POE

Harga : Rp 2.373.000,00



TP-LINK ES220GP OMADA merupakan switch layer 2 dengan casing Desktop/Rackmount, 18 port Gigabit PoE+ (16 port support 802.3af/at PoE+) dengan max PoE budget 150 W (up to 30 W per port) dan 2 port SFP 1G.

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial

 **08112039555**

- 18 port RJ45 10/100/1000Mbps (16 PoE+ yang sesuai dengan standar 802.3af/at)
- 2 Slot SFP Gigabit
- Anggaran PoE 150W, dengan daya hingga 30W untuk setiap port PoE
- Mudah Digunakan: Mendukung plug-and-play untuk konektivitas instan dan konfigurasi sederhana untuk fitur tambahan.
- Manajemen Cloud Terpusat melalui web atau aplikasi Omada
- Pencegahan Loop Otomatis, VLAN, dan IGMP Snooping
- Desain tanpa kipas untuk pengoperasian yang senyap
- Casing logam yang tahan lama dan desain pemasangan rak



Spesifikasi

Model	ES220GP
HARDWARE FEATURES	
Interface	• 18× 10/100/1000 Mbps PoE+ RJ45 Ports (16× 802.3af/at-compliant PoE+) • 2× Gigabit SFP Slots • Auto-Negotiation/Auto MDI/MDIX
Fan	Fanless
Physical Security Lock	Yes

Power Supply	100-240V AC, 50/60Hz 2.5A
PoE Ports (RJ45)	• Standard: 802.3af PoE and 802.3at PoE+ compliant • PoE Ports: 16 Ports • PoE Budget: 150W available for all PoE+ ports, 30W max per port • Fast PoE & Perpetual PoE • PoE Auto Recovery
Dimensions (W x D x H)	11.6 × 7.1 × 1.7 in (294 × 180 × 44 mm)
Surge Protection	±6 kV
Mounting	Desktop/Rackmount
Max. Power Consumption	14.01 W (with no PD connected) @ 220V/50Hz 25 °C 16.25 W (with no PD connected) @ 110V/60Hz 25 °C 176.87 W (with 150 W PD connected) @ 220V/50Hz 25 °C 182.43 W (with 150 W PD connected) @ 110V/60Hz 25 °C
Max. Heat Dissipation	47.64 BTU/hr (with no PD connected) @ 220V/50Hz 25 °C 55.25 BTU/hr (with no PD connected) @ 110V/60Hz 25 °C 601.36 BTU/hr (with 150 W PD connected) @ 220V/50Hz 25 °C 620.27 BTU/hr (with 150 W PD connected) @ 110V/60Hz 25 °C
Packet Buffer Memory	4 Mbit
Switching Capacity	40 Gbps
Packet Forwarding Rate	29.76 Mpps
MAC Address Table	8K
Jumbo Frame	15 KB
Transmission Method	Store and Forward
SOFTWARE FEATURES	
Quality of Service	• Port-based/802.1p/DSCP QoS • 8 Priority Queues • Priority Schedule Mode - WRR (Weighted Round Robin) • Queue Weight Config • Bandwidth Control - Port-Based Rating Limit • Storm Control - Multiple Control Modes (kbps/pps) - Broadcast/Multicast/Unknown-Unicast Control

L2 Features	• Static Link Aggregation • Loop Prevention / Loopback Detection • Flow Control - 802.3x Flow Control • Mirroring - Port Mirroring - One-to-One - Many-to-One - Ingress/Egress/Both • Port Statistics - Port Mirror Status - Traffic Statistics • 802.1ab LLDP
L2 Multicast	• IGMP Snooping - IGMP v1/v2/v3 Snooping - Fast Leave
VLAN	• MTU VLAN • Port-Based VLAN • 802.1Q Tag VLAN - Max 32 VLAN Groups - 4K VID
OTHERS	
Certification	CE, FCC
Package Content	• ES220GP • Power Cord • Mounting Brackets • Rubber Feet • Screws • Installation Guide
Environment	• Operating Temperature: -5-40C (23-104F) • Storage Temperature: -40-70C (-40-158F) • Operating Humidity: 10-90% RH non-condensing • Storage Humidity: 5-90% RH non-condensing

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1604/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com