

TP-LINK TL-SG1428PE OMADA 28-Port Gigabit Easy Smart Switch with 24-Port PoE+

Kode : TL-SG1428PE

Brand : TP-Link Omada

Jenis : Switch Managed POE

Harga : Rp 3.730.000,00



TP-LINK TL-SG1428PE OMADA merupakan switch layer 2 dengan casing Rackmount dilengkapi 26 port 10/10/1000 Mbps (24 port support PoE+ up to 250 W) dan 2 port SFP 1G.

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial

 **08112039555**

- Switch dengan 24 Port RJ45 PoE+ 10/100/1000Mbps dan 2 Slot SFP
- Anggaran daya PoE mencapai 250 W, menjadikannya ideal untuk sistem pengawasan bisnis kecil hingga menengah.
- Mode Prioritas membantu menjamin kualitas aplikasi sensitif seperti pemantauan video.
- PoE Auto Recovery memungkinkan sistem untuk memperbaiki diri sendiri guna menjamin pengoperasian perangkat yang terhubung melalui PoE secara stabil.
- QoS (Quality of Service) bertujuan untuk memberikan pengalaman berselancar internet yang lancar, sedangkan IGMP Snooping mampu mengoptimalkan lalu lintas untuk IPTV.
- Manajemen daya cerdas dapat melindungi sakelar dari kelebihan beban.

BACK VIEW



Spesifikasi

Model	TL-SG1428PE
HARDWARE FEATURES	
Interface	26x 10/100/1000 Mbps RJ45 Ports 2x Gigabit SFP Ports
Fan	2 Fans
Physical Security Lock	Yes
Power Supply	100-240V AC, 50/60 Hz
PoE Ports (RJ45)	Standard: 802.3at/802.3af compliant PoE+ Ports: 24 Ports Power Supply: 250 W
Dimensions (W x D x H)	17.3 × 8.7 × 1.73 in (440 × 220 × 44 mm)
Mounting	Rackmountable
Max. Power Consumption	27 W (220/50Hz. no PD connected) 304.7 W (220/50Hz. with 250 W PD connected)
Max. Heat Dissipation	92.07 BTU/h (no PD connected) 1039.03 BTU/h (with 250 W PD connected)
Packet Buffer Memory	4.1Mbit
Switching Capacity	56 Gbps
Packet Forwarding Rate	41.7 Mpps
MAC Address Table	8K

Jumbo Frame	9 KB
SOFTWARE FEATURES	
Quality of Service	Support Port-based 802.1p/DSCP priority Support 4 priority queues Rate Limit Storm Control
L2 Features	IGMP Snooping V1/V2/V3 Static Link Aggregation Port Mirroring Cable Diagnostics Loop Prevention PoE Auto Recovery
VLAN	Supports up to 32 VLANs simultaneously (out of 4K VLAN IDs) MTU/Port/Tag VLAN
Transmission Method	Store-And-Forward
OTHERS	
Certification	CE, FCC
Package Content	TL-SG1428PE Power Cord Installation Guide Rackmount Kit Rubber Feet
Environment	• Operating Temperature: 0~50C (32~122F) • Storage Temperature: -40~70C (-40~158F) • Operating Humidity: 10~90% RH non-condensing • Storage Humidity: 5~90% RH non-condensing

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1669/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com