

TP-LINK TL-SG1218MPE OMADA 16-Port Gigabit Easy Smart PoE+ Switch with 2 SFP Slots

Kode : TL-SG1218MPE
Brand : TP-Link Omada
Jenis : Switch Managed POE
Harga : Rp 3.160.000,00



TP-LINK TL-SG1218MPE OMADA merupakan switch layer 2 dengan casing Rackmount dilengkapi 16 port 10/10/1000 Mbps support PoE+ (up to 250 W) dan 2 port Combo SFP 1G.

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial

 **08112039555**

- Switch dengan 16 Port RJ45 PoE+ 10/100/1000Mbps dan 2 Slot SFP
- Anggaran daya PoE mencapai 250 W, menjadikannya ideal untuk sistem pengawasan bisnis kecil hingga menengah.
- Prioritas Port mampu menjamin kualitas aplikasi sensitif seperti monitor video.
- Manajemen daya cerdas dapat melindungi sakelar dari kelebihan beban.
- QoS ditujukan untuk pengalaman berselancar internet yang lancar, dan IGMP Snooping mampu mengoptimalkan lalu lintas untuk IPTV.

BACK VIEW

Spesifikasi

Model	TL-SG1218MPE
HARDWARE FEATURES	
Interface	• 16× 10/100/1000 Mbps PoE+ RJ45 Ports (Auto Negotiation/Auto MDI/MDIX) • 2× 10/100/1000 Mbps non-PoE RJ45 Ports (Auto Negotiation/Auto MDI/MDIX) • 2× Combo Gigabit SFP Ports
Fan	2 Fans
Physical Security Lock	Yes
Power Supply	100-240V AC, 50/60 Hz
PoE Ports (RJ45)	Standard: 802.3at/802.3af compliant • PoE+ Ports: Ports 1-16 • Power Supply: 250 W
Dimensions (W x D x H)	17.3 × 7.1 × 1.7 in (440 × 180 × 44 mm)
Mounting	Rackmountable
Max. Power Consumption	• 21.4 W (220/50Hz. no PD connected) • 296.3 W (220/50Hz. with 250 W PD connected)
Max. Heat Dissipation	• 72.97 BTU/h (no PD connected) • 1010.38 BTU/h (with 250 W PD connected)
Packet Buffer Memory	4.1Mbit
Switching Capacity	36 Gbps

Packet Forwarding Rate	26.78 Mbps
MAC Address Table	8K
Jumbo Frame	10 KB
SOFTWARE FEATURES	
Quality of Service	Support Port-based 802.1p/DSCP priority Support 4 priority queues Rate Limit Storm Control
L2 Features	IGMP Snooping V1/V2/V3 Static Link Aggregation Port Mirroring Cable Diagnostics Loop Prevention PoE Auto Recovery
VLAN	Supports up to 32 VLANs simultaneously (out of 4K VLAN IDs) MTU/Port/Tag VLAN
Transmission Method	Store-And-Forward
OTHERS	
Certification	CE, FCC
Package Content	• TL-SG1218MPE • Power Cord • Installation Guide • Rackmount Kit • Rubber Feet
Environment	• Operating Temperature: 0~50C (32~122F) • Storage Temperature: -40~70C (-40~158F) • Operating Humidity: 10~90% RH non-condensing • Storage Humidity: 5~90% RH non-condensing

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1670/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com