

TP-LINK TL-SG1016PE OMADA 16-Port Gigabit Easy Smart Switch with 8-Port PoE+

Kode : TL-SG1016PE

Brand : TP-Link Omada

Jenis : Switch Managed POE

Harga : Rp 2.107.000,00



TP-LINK TL-SG1016PE OMADA merupakan switch layer 2 dengan casing Rackmount/Desktop dilengkapi 16 port 10/10/1000 Mbps (8 port support PoE+ up to 150 W).

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial

 **08112039555**

- 16 port RJ45 10/100/1000Mbps
- Dilengkapi dengan 8 port yang mendukung PoE+ untuk mentransfer data dan daya melalui satu kabel
- Dengan total anggaran daya PoE sebesar 150 W, hingga 30 W per port
- Kompatibel dengan perangkat yang sesuai dengan standar IEEE 802.3af/at
- Secara otomatis melakukan reboot perangkat bertenaga PoE Anda yang terputus atau tidak responsif dengan PoE Auto Recovery
- Pengaturan jaringan yang sederhana di atas konektivitas plug-and-play
- Antarmuka pengguna berbasis web dan utilitas manajemen menyederhanakan konfigurasi

BACK VIEW



Spesifikasi

Model	TL-SG1016PE
HARDWARE FEATURES	
Interface	16× 10/100/1000 Mbps RJ45 Ports AUTO Negotiation/AUTO MDI/MDIX
Fan	Fanless
Physical Security Lock	Yes
Power Supply	100-240V AC, 50/60 Hz
PoE Ports (RJ45)	Standard: 802.3 af/at compliant PoE Ports: Port 1 to Port 8 PoE Power Budget: 150 W
Dimensions (W x D x H)	11.6×7.1×1.7 in (294×180×44 mm)
Mounting	Rack Mountable/ Desktop
Max. Power Consumption	13.07 W (220 V/50 Hz with no PD connected) 173.88 W (220 V/50 Hz with 150 W PD connected)
Max. Heat Dissipation	44.438 BTU/h (220 V/50 Hz with no PD connected) 591.192 BTU/h (220 V/50 Hz with 150 W PD connected)
Packet Buffer Memory	4.1Mbit
Switching Capacity	32 Gbps
Packet Forwarding Rate	23.8 Mbps
MAC Address Table	8K
Jumbo Frame	10 KB
SOFTWARE FEATURES	
Quality of Service	Support Port-based 802.1p/DSCP priority Support 4 priority queues Rate Limit Storm Control
L2 Features	IGMP Snooping V1/V2/V3 Static Link Aggregation Port Mirroring Cable Diagnostics Loop Prevention
VLAN	Supports up to 32 VLANs simultaneously (out of 4K VLAN IDs) MTU/Port/Tag VLAN

Transmission Method	Store-And-Forward
OTHERS	
Certification	CE, FCC
Package Content	TL-SG1016PE Power Cord Installation Guide Rackmount Kit Rubber Feet
Environment	• Operating Temperature: 0~45C (32~113F) • Storage Temperature: -40~70C (-40~158F) • Operating Humidity: 10-90% RH non-condensing • Storage Humidity: 5-90% RH non-condensing

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1671/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com