CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

Solar Charger SCC-600MPPT



Kode : SCC-600MPPT
Brand : Maruson
Jenis : Power Inverter
Harga : Rp 1.890.000,00
~~Rp 2.225.000,00~~

SCC-600MPPT adalah sebuah solar charger controller dengan kapasitas 600watt dan kemampuan charging 25A. Produk ini bisa digunakan pada battery 12/24v (auto sensing).
*tidak termasuk battery
****Gunakan battery yang dirancang untuk SHS (Solar Home System) / Deep-cycle VRLA**

Penawaran **Harga Spesial**
08112039555



www.citraweb.com

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com



www.citraweb.com

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com



www.citraweb.com

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com



www.citraweb.com

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com



www.citraweb.com

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com



www.citraweb.com

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com



www.citraweb.com

Features :

- Intelligent continuous maximum power point tracking technology
- Microprocessor controlled
- Automatic battery voltage detection
- Three-stage charging optimizes battery performance
- Auto load detection
- Multifunction LCD displays detailed information
- Reverse polarity protection of solar panel and battery
- Short circuit and overload protection
- Optional IP 43 protection for outdoor and harsh environment
- Optional RS-232/RJ45 ports for remote monitoring

Battery Recomendation :

- Solar Home System Battery
- Deep Cycle VRLA Battery
- VRLA Gel / AGM Battery

Specification :

Model	SCC-600MPPT

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

INPUT	
MPPT Range @ Operating Voltage	30 V ~ 66 V @ 24V
Max PV Array Open Circuit Voltage	75 V
Max PV Array Power	600W
Max Current	18 A
OUTPUT	
Nominal Battery Voltage	24 V
Connected Battery Type	Sealed lead acid, vented, Gel, NiCd battery
Max Charging Current	25 A
Ripple Voltage	< +/- 1 V
Max Efficiency	97.80%
Standby Power Consumption	2 W
Charging Method	Three stages : bulk, absorption, and floating
PROTECTION	
Overload Protection	> 110% : audible alarm
Overcharge Protection	Yes
Polarity Reversal Protection @ Solar Cell & Battery	Yes
INDICATOR	
LCD Panel	LCD panel indicating solar power, output power, battery voltage, charging current, and fault conditions
LED Display	Three indicators for solar, charging, and load status
PHYSICAL	
Dimension (DxWxH) mm	220 x 170 x57.5
Net Weight kg	2
Connector	Input/Output terminal block
Type of Mechanical Protection	IP 43

www.citraweb.com

Manual : SCC-600MPPT-Manual.pdf

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/760/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com